

Date: 31.10.2025

Installation column 124x110-9010, 2800 mm, 2-sided, aluminium, pure white



Product description

Floor/ceiling service pole of aluminium with two 76.5 mm wide fixing tracks for device installation of commercially available switch ranges in combination with accessory mounting boxes or M45 built-in devices with the aid of front-locking mounting frames, cable entry through the floor or via the ceiling, consisting of two bases with a DIN rail for snap-in mounting of a partition wall of plastic for separating cables and two covers as pole body (height 2. 800 mm), a permanently mountable base plate (width: 200 mm, depth: 200 mm, material thickness: 17 mm), a top plate for fastening the telescopic unit and a universal telescope for clamping fastening. Potential equalisation and earthing measures must be carried out professionally. The specified length corresponds to the length of the column body.

Basic data

Item number	18671
Product group	30-floor and ceiling installation
Packing unit	1 piece
EAN code	4018475331006
Tariff number	76109090

Technical features

Pillar shape	rectangular
Model	double-sided
Prewired	no
Height levelling	300 mm
Column height	2800 - 2800 mm
Column depth	124 mm
Column width	110 mm
Number of usable covers	2
Cover width	80 mm
Cover depth	15 mm
Type of fastening	telescope
Place variable	no
Cable entry	top/bottom
Through-going profile	yes
Material installation column	aluminium
Material installation column halogen free	yes
Surface protection column	coated
Colour column	white
RAL-number column	9010
Material cover	aluminium
Material cover halogen free	yes
Cover surface	coated
RAL-number cover	9010
Useful cross section	12010 mm ²
Floor mounting possible	yes

Ceiling mounting	yes
------------------	-----