

Date: 31.10.2025

Installation column 124x130-9010, 3000 mm, 2-sided, aluminium, pure white



Product description

Floor/ceiling service pole of aluminium with two 76.5 mm wide fixing tracks for device installation of commercially available switch ranges in combination with accessory mounting boxes or M45 built-in devices with the aid of front-locking mounting frames, cable entry through the floor or via the ceiling, consisting of two bases with a DIN rail for snap-in mounting of a partition wall of plastic for separating cables and two covers as pole body (height 3. 000 mm), a permanently mountable base plate (width: 200 mm, depth: 200 mm, material thickness: 17 mm), a top plate for fastening the telescopic unit and a universal telescope for clamping fastening. Potential equalisation and earthing measures must be carried out professionally. The specified length corresponds to the length of the column body.

Basic data

Product group 30-floor and ceiling installation	
Froduct group 30-noor and centing installation	
Packing unit 1 piece	
EAN code 4018475331051	
Tariff number 76109090	

Technical features

Pillar shape	rectangular
Model	double-sided
Prewired	no
Height levelling	300 mm
Column height	3000 - 3000 mm
Column depth	124 mm
Column width	130 mm
Number of usable covers	2
Cover width	80 mm
Cover depth	15 mm
Type of fastening	telescope
Place variable	no
Cable entry	top/bottom
Through-going profile	yes
Material installation column	aluminium
Material installation column halogen free	yes
Surface protection column	anodised
Colour column	white
RAL-number column	9010
Material cover	aluminium
Material cover halogen free	yes
Cover surface	coated
RAL-number cover	9010
Useful cross section	14370 mm²
Floor mounting possible	yes



Ceiling mounting yes