


Date: 24.04.2026

Installation trunking FB 60x130-7030, PVC, with base perforation, grey



Product description

PVC installation trunking according to DIN EN 50085-2-1 for cable routing on walls and ceilings, consisting of completely overlapping cover and base with double-row base perforation for fastening and a DIN rail for the installation of device installation boxes as well as snap-in partition walls, 4 freely movable cable clips included per 2 metre. **Note:** Sound and fire protection measures must be carried out professionally.

Basic data

Item number	1010
Product group	10-Cable routing
Packing unit	10 meters
EAN code	4018475010109
Tariff number	39259020

Technical features

Height	62 mm
Width	130 mm
Length	2000 mm
Useful cross section	6890 mm ²
Material	plastic
Material quality	Polyvinyl chloride (PVC)
Halogen free	no
Anti-bacterial treatment	no
Surface protection	untreated
Suitable for circuit integrity	no
Colour	grey
Transparent	no
RAL-number	7030
Number of permanent partitions	0
Number of plug-in partitions	1
Type of fastening	Bottom perforation
Cover model	loose
With cable fixing clip	yes
With protective foil	no
With duct connector	no
Delivery on roll	no
Pre-stamping	no
Degree of protection (IP)	IP30
Impact strength	IK10
Operating temperature	from -5 to 60 °C