


Date: 24.04.2026

Installation trunking LFG 25x40-7030, PVC, with base perforation, grey



Product description

PVC installation trunking according to DIN EN 50085-2-1 for cable laying on walls and ceilings, consisting of a completely overlapping cover and base with single-row base perforation for fastening.

Note: Sound and fire protection measures must be carried out professionally.

Basic data

| | |
|---------------|------------------|
| Item number | 1003 |
| Product group | 10-Cable routing |
| Packing unit | 40 meters |
| EAN code | 4018475010031 |
| Tariff number | 39259020 |

Technical features

| | |
|--------------------------------|--------------------------|
| Height | 27 mm |
| Width | 40 mm |
| Length | 2000 mm |
| Useful cross section | 870 mm ² |
| Material | plastic |
| Material quality | Polyvinyl chloride (PVC) |
| Halogen free | no |
| Anti-bacterial treatment | no |
| Surface protection | other |
| Suitable for circuit integrity | no |
| Colour | grey |
| Transparent | no |
| RAL-number | 7030 |
| Number of permanent partitions | 0 |
| Number of plug-in partitions | 0 |
| Type of fastening | Bottom perforation |
| Cover model | loose |
| With cable fixing clip | no |
| With protective foil | no |
| With duct connector | no |
| Delivery on roll | no |
| Pre-stamping | no |
| Degree of protection (IP) | IP30 |
| Impact strength | IK08 |
| Operating temperature | from -5 to 60 °C |