


Date: 24.04.2026

Installation trunking LFG 40x60-80184, PVC-metallic, with base perforation, bronze



Product description

PVC installation trunking according to DIN EN 50085-2-1 for cable routing on walls and ceilings, consisting of completely overlapping cover and base with double-row base perforation for fastening, 4 freely adjustable cable retaining clips are included per 2 metre. **Note:** Sound and fire protection measures must be carried out professionally.

Basic data

Item number	3662
Product group	10-Cable routing
Packing unit	6 meters
EAN code	4018475348394
Tariff number	39259020

Technical features

Height	40 mm
Width	57 mm
Length	2000 mm
Useful cross section	1854 mm ²
Material	plastic
Material quality	Polyvinyl chloride (PVC)
Halogen free	no
Anti-bacterial treatment	no
Surface protection	other
Suitable for circuit integrity	no
Colour	Bronze
Transparent	no
RAL-number	80184
Number of permanent partitions	0
Number of plug-in partitions	0
Type of fastening	Bottom perforation
Cover model	loose
With cable fixing clip	yes
With protective foil	no
With duct connector	no
Delivery on roll	no
Pre-stamping	no
Degree of protection (IP)	IP30
Impact strength	IK10
Operating temperature	from -5 to 60 °C