


Date: 24.04.2026

## Installation trunking LFS 60x60, steel, without base perforation, zinc



### Product description

installation trunking made of sheet steel according to DIN EN 50085-2-1 for cable routing on walls and ceilings, consisting of completely overlapping cover and base. (Lower sections available with floor perforation and permanently welded partition wall on request) Freely movable cable clips must be ordered separately. **Note:** Potential equalisation, earthing, sound and fire protection measures must be carried out professionally.

### Basic data

|               |                  |
|---------------|------------------|
| Item number   | 2302             |
| Product group | 10-Cable routing |
| Packing unit  | 8 meters         |
| EAN code      | 4018475023024    |
| Tariff number | 73089059         |

### Technical features

|                                |                         |
|--------------------------------|-------------------------|
| Height                         | 60 mm                   |
| Width                          | 60 mm                   |
| Length                         | 2000 mm                 |
| Useful cross section           | 3481 mm <sup>2</sup>    |
| Material                       | Steel                   |
| Material quality               | other                   |
| Halogen free                   | yes                     |
| Anti-bacterial treatment       | no                      |
| Surface protection             | continuously galvanised |
| Suitable for circuit integrity | no                      |
| Colour                         | zinc                    |
| Transparent                    | no                      |
| Number of permanent partitions | 0                       |
| Number of plug-in partitions   | 0                       |
| Type of fastening              | other                   |
| Cover model                    | loose                   |
| With cable fixing clip         | no                      |
| With protective foil           | no                      |
| With duct connector            | no                      |
| Delivery on roll               | no                      |
| Pre-stamping                   | no                      |
| Degree of protection (IP)      | IP30                    |
| Impact strength                | IK10                    |
| Operating temperature          | from -5 to 60 °C        |