Date: 06.11.2026

# Matrix installation trunking Mini 13x25mm-9010, PVC, for mounting on top, pure white



## Product description

PVC installation trunking according to DIN EN 50085-2-1 for cable laying on walls and ceilings, consisting of a completely overlapping cover and base. A solution for achieving IP41 protection is available on request. **Note:** Surface-mounted profile for extending existing installations – mounted on top of an existing profile and to be used in conjunction with article no. 11021.

## Basic data

| | |
|---|---|
| Item number | 11022 |
| Product group | 10-Cable routing |
| Packing unit | 20 meters |
| EAN code | 4018475349544 |
| Tariff number | 39259020 |

## Technical features

| | |
|---|---|
| Height | 13 mm |
| Width | 25 mm |
| Length | 2000 mm |
| Useful cross section | 240.9 mm² |
| Material | plastic |
| Halogen free | no |
| Anti-bacterial treatment | no |
| Surface protection | other |
| Suitable for circuit integrity | no |
| Colour | white |
| Transparent | no |
| RAL-number | 9010 |
| Number of permanent partitions | 0 |
| Number of plug-in partitions | 0 |
| Type of fastening | Bottom perforation |
| Cover model | loose |
| With cable fixing clip | no |
| With protective foil | no |
| With duct connector | no |
| Delivery on roll | no |
| Pre-stamping | no |
| Degree of protection (IP) | IP30 |
| Impact strength | IK07 |
| Operating temperature | from -5 to 60 °C |