Date: 25.11.2026

On-floor trunking ABK 12x50-9005, PVC, 2 chambers, ribbed back side, black



Product description

On-floor installation duct made of PVC according to DIN EN 50085-2-2 for the protection of cables and to avoid tripping hazards caused by cables lying on the floor, consisting of a base with two separate chambers and an overlapping cover with a fluted surface structure that is less sensitive to scratches. The profile can be walked on as well as stepped on and can withstand vertical loads of ~ 77 kg (750 N). **Note:** The colour of the bases may vary due to production.

Basic data

Item number	6680
Product group	70-Residential installation
Packing unit	54 meters
EAN code	4018475247635
Tariff number	39259020

Technical features

Width	50 mm
Height	12 mm
Number of channels	2
Length	2000 mm
Material	plastic
Halogen free	no
Anti-bacterial treatment	no
Colour	black
RAL-number	9005
Self-adhesive	no
Sealing lip	no
With anti-slip layer	no
Max. load capacity	0.077 t
Degree of protection (IP)	IP30
Impact strength	IK08
With cover cap	no
Permitted cable diameter	from 6 to 8 mm
Mounting perforation in bottom	no
Slotted hole	no
With fixation	no
Demountable	yes
Reflective	no
Fuel- and oil resistant	yes
Resistance to vertical load applied in a small surface according IEC 61084-2-2	750
Resistance to vertical load applied in a large surface according IEC 61084-2-2	750
Suitable for car	no
Suitable for truck	no

Bending strength	Rigid