Date: 09.11.2026

Socket double KSE/50-2-9006, with frame, DIN-rail, alu



Product description

Double socket outlet including mounting box, cable connection via plug-in terminals, 2-pole, 16 A/250 V~, with connection terminals according to VDE 0620, suitable for 2 angle or surface plugs, with increased contact protection, with labelling field 7x64mm, for installation in trunking with a DIN rail and a height of 60 mm.

Basic data

Item number	21284
Product group	40-Installation devices
Packing unit	4 s
EAN code	4018475281516
Tariff number	85366990

Technical features

Model	Earthing pin
With signal lamp	no
Imprint/indication	other
Connection type	push-in clamp
With hinged lid	no
With enhanced contact protection	yes
Label space/information surface	yes
Colour	aluminium
Transparent	no
Lockable	no
Insulated mounting	no
With orientation lighting	no
Special power supply	other
Mounting method	wall duct
Type of fastening	Mounting with screw
Material	plastic
Halogen free	no
Surface protection	untreated
Surface finishing	Glossy
With on/off switch	no
With loop through function	no
Nominal current	16 A
Nominal voltage	250 V
Suitable for degree of protection (IP)	other
Impact strength	other
Width of device	152 mm
Height of device	81 mm
Depth of device	50 mm

Compatible with Apple HomeKit	no
Compatible with Google Assistant	no
Compatible with Amazon Alexa	no
Mounting direction	Horizontal
Number of ports USB-A	0
Number of socket outlets	2
Colour of switch operator	aluminium
With Wi-Fi signal repeater	no
With built-in bluetooth speaker	no
Compliant with UK Building Regulations Part M	no