

Date: 24.04.2026

## Socket double KSE/P-2-3001, with frame, front-locking, red



### Product description

Double socket outlet including mounting box, cable connection via plug-in terminals, 2-pole, 16 A/250 V~, with connection terminals to VDE 0620, suitable for 2 angled or flat plugs, with increased contact protection, with labelling field 7x64mm, for installation in wall trunking with a 76.5 mm wide fixing track.

### Basic data

|               |                         |
|---------------|-------------------------|
| Item number   | 36785                   |
| Product group | 40-Installation devices |
| Packing unit  | 1 piece                 |
| EAN code      | 4018475270664           |
| Tariff number | 85366990                |

### Technical features

|  |                     |
|--|---------------------|
| Model                                  | Earthing pin        |
| With signal lamp                       | no                  |
| Imprint/indication                     | other               |
| Connection type                        | push-in clamp       |
| With hinged lid                        | no                  |
| With enhanced contact protection       | yes                 |
| Label space/information surface        | yes                 |
| Colour                                 | red                 |
| RAL-number (similar)                   | 3003                |
| Transparent                            | no                  |
| Lockable                               | no                  |
| With orientation lighting              | no                  |
| Special power supply                   | other               |
| Mounting method                        | wall duct           |
| Type of fastening                      | Mounting with screw |
| Material                               | plastic             |
| Material quality                       | Thermoplastic       |
| Halogen free                           | no                  |
| Surface protection                     | untreated           |
| Surface finishing                      | Glossy              |
| Nominal current                        | 16 A                |
| Nominal voltage                        | 250 V               |
| Suitable for degree of protection (IP) | other               |
| Impact strength                        | other               |
| Width of device                        | 152 mm              |
| Height of device                       | 81 mm               |
| Depth of device                        | 44 mm               |
| Compatible with Apple HomeKit          | no                  |

|   |            |
|---|------------|
| Compatible with Google Assistant              | no         |
| Compatible with Amazon Alexa                  | no         |
| Mounting direction                            | Horizontal |
| Number of ports USB-A                         | 0          |
| Number of socket outlets                      | 2          |
| With Wi-Fi signal repeater                    | no         |
| With built-in bluetooth speaker               | no         |
| Compliant with UK Building Regulations Part M | no         |
| Colour of switch operator                     | red        |