

Date: 24.04.2026

## Trunking Mini snap 6x7-trans, adhesive, for cables 4 mm, transparent



### Product description

PVC trunking with double-sided adhesive foam tape for laying cables on walls and ceilings. **Note:** For long-term use, we recommend nailing or screwing.

### Basic data

|               |                             |
|---------------|-----------------------------|
| Item number   | 1536                        |
| Product group | 70-Residential installation |
| Packing unit  | 50 meters                   |
| EAN code      | 4018475015364               |
| Tariff number | 39259020                    |

### Technical features

|                                |                          |
|--------------------------------|--------------------------|
| Height                         | 6 mm                     |
| Width                          | 7 mm                     |
| Length                         | 2000 mm                  |
| Useful cross section           | 27 mm <sup>2</sup>       |
| Material                       | plastic                  |
| Material quality               | Polyvinyl chloride (PVC) |
| Halogen free                   | no                       |
| Anti-bacterial treatment       | no                       |
| Surface protection             | other                    |
| Suitable for circuit integrity | no                       |
| Colour                         | other                    |
| Transparent                    | yes                      |
| Number of permanent partitions | 0                        |
| Number of plug-in partitions   | 0                        |
| Type of fastening              | adhesive                 |
| Cover model                    | loose                    |
| With cable fixing clip         | no                       |
| With protective foil           | no                       |
| With duct connector            | no                       |
| Delivery on roll               | no                       |
| Pre-stamping                   | no                       |
| Degree of protection (IP)      | IP30                     |
| Operating temperature          | from -5 to 60 °C         |